

## ORIGINAL CLAIMS

### MULTISTANDARD VIDEO DECODER AND DECOMPRESSION SYSTEM FOR PROCESSING ENCODED BIT STREAMS INCLUDING STORING DATA AND METHODS RELATING THERETO

USSN: 09/771,062

Status: Pending

Our Reference: 94100414(EP)USC1X1C1D3 PDDD

Total Claims: 7

1           1.     A method of storing data, comprising:  
2           receiving a sequence of data words of a first predetermined width and different  
3     respective formats;  
4           splitting the data words of the received sequence to form new data words of a  
5     new sequence, the new data words having a second predetermined width;  
6           packing the consecutive new data words consecutively in a token buffer of a  
7     second width without holes between the packed new data words; and  
8           unpacking the data words to reproduce the new sequence of new data words.

1           2.     The method of claim 1, further comprising:  
2           writing a block of data from the token buffer to a random access memory device  
3     configured to store words of the second width.

1           3.     The method of claim 1, further comprising:  
2           expanding out run length code in the unpacked words.

1           4.     An inverse modeler, comprising:  
2           a data unpacker to unpack data words received from an input terminal to a  
3     different length format;  
4           a data expander coupled to the data unpacker; and  
5           a data padder to pad data tokens received from the expander.

## ORIGINAL CLAIMS

### MULTISTANDARD VIDEO DECODER AND DECOMPRESSION SYSTEM FOR PROCESSING ENCODED BIT STREAMS INCLUDING STORING DATA AND METHODS RELATING THERETO

USSN: 09/771,062

Status: Pending

Our Reference: 94100414(EP)USC1X1C1D3 PDDD

Total Claims: 7

1           5.     The inverse modeler of claim 4, wherein the data expander expands out  
2 run length codes into runs of zeros followed by a level in the packed data.

1           6.     The inverse modeler of claim 5, wherein the data padder pads the last  
2 word of the expanded tokens.

1           7.     The inverse modeler of claim 4, wherein the data unpacker deletes data  
2 between a flush signal and a block end signal.

P:\ABG\PPD\IPDD\941004--(EP)USC1X1C1D3\claims\_original.doc